


MODEL: BF-C1250

400V | 1500rpm | 50Hz



ESP Standby Power	1250 kVA	PRP Prime Power	N/A
ENGINE	CCEC Cummins KTA38-G9	ALTERNATOR	STAMFORD S6L1D-F4

GENERAL FEATURES

Engine: CCEC Cummins KTA38-G9

Alternator: single bearing, IP23, insulation class H

40°C radiator, fans are driven by belt, with safety guard

Dry type air filter, fuel filter & oil filter

Vibration damper

Standard control panel

24V charging alternator

Exhaust bellows, elbows, flange & muffler

Lead-acid batteries, rack and cables

User manual

MODEL: BF-C1250

400V | 1500rpm | 50Hz

GENERATOR RATINGS

Voltage	Hz	Phase	PF (COSΦ)	Standby Amps	Standby Ratings (kW / kVA)	Prime Ratings (kW / kVA)
440/254	50	3	0.8	1640	1000/1250	N/A
415/240	50	3	0.8	1739	1000/1250	N/A
400/230	50	3	0.8	1804	1000/1250	N/A
380/220	50	3	0.8	1899	1000/1250	N/A

Prime Power (PRP): Prime power is available for an unlimited number of annual hours in variable load application, in accordance with GB/T2820 (eqv ISO 8528) ; A 10% overload capability is available for a period of 1 hour within a 12-hour period of operation.

Standby Power Rating (ESP): The standby power rating is applicable for supplying emergency power for the duration of a utility power interruption. No overload, utility parallel or negotiated outage operation capability is available at this rating.

SALES PROMISES

Baifa Power provides a full line of brand new and high quality products. Each and every unit is strictly factory tested.

Warranty is according to our standard conditions: 15 months from the date BAIFA sold to the first buyer or one year after installation or 1000 running hours (accumulated), whichever comes first.

Service and parts are available from Baifa Power or distributors in your location.

MODEL: BF-C1250

400V | 1500rpm | 50Hz

ENGINE SPECIFICATION

Manufacturer / Model	CCEC Cummins KTA38-G9
Air intake system	Turbo, Air/Water cooling
Fuel system	PT type fuel pump, EFC
Cylinder arrangement	12 in V
Displacement	37.8L
Bore and stroke	159*159 (mm)
Compression ratio	13.9:1
Rated speed	1500rpm
Max. Standby power at rated speed	1089KW/1481HP
Governor type	Electronic

Exhaust System

Exhaust gas flow	217.5 m ³ /min
Exhaust temperature	552 °C
Max back pressure	10kPa

Air Intake System

Max intake restriction	6.23kPa
Combustion air flow	79.86 m ³ /min
Air flow required for radiator	1140 m ³ /min

**MODEL: BF-C1250****400V | 1500rpm | 50Hz****Fuel System**

Fuel consumption @ 100% (Standby Power) Load	193 g/kWh	243 L/h
Fuel consumption @ 75% (Standby Power) Load	N/A	N/A
Fuel consumption @ 50% (Standby Power) Load	N/A	N/A

Oil System

Total oil capacity	135L
Oil consumption	≤4g/kwh
Oil sump capacity	121~151L

Cooling System

Coolant capacity	280L
Max water temperature	104℃



MODEL: BF-C1250

400V | 1500rpm | 50Hz

ALTERNATOR SPECIFICATION

Industrial alternators meet the requirements of the relevant parts of the BS5000, VDE 0530, NEMA MG1-22, IEC34, CSA 22.2-100 and AS1359.

Alternator Data

Number of Phase	3
Connecting Type	3 Phase and 4 Wires, Y type connecting
Number of Bearing	1
Power Factor	0.8
Protection Class	IP23
Altitude	≤1000m
Exciter Type	Brushless exciting
Insulation Class/Temperature Rise	H/H
Telephone Influence Factor (TIF)	<50
THF	<2%
Alternator Capacity	1150kVA
Alternator Efficiency	95.5%

MODEL: BF-C1250

400V | 1500rpm | 50Hz

GENERATING SET DATA

Related range of voltage setting	$\geq \pm 5\%$
Steady-state voltage deviation	$\leq \pm 1\%$
Transient voltage deviation (100 % sudden power decrease)	$\leq +25\%$
Transient voltage deviation (sudden power increase)	$\leq -20\%$
Voltage recovery time (100 % sudden power decrease)	$\leq 6S$
Voltage recovery time (sudden power increase)	$\leq 6S$
Related range of frequency setting	0-5% adjustable
Steady-state frequency band	$\leq 1.5\%$
Transient frequency deviation (100 % sudden power decrease)	$\leq +12\%$
Transient frequency deviation (sudden power increase)	$\leq -10\%$
Frequency recovery time (100 % sudden power decrease)	$\leq 5S$
Frequency recovery time (sudden power increase)	$\leq 5S$

STANDARD FEATURES

Standard auto control system	Exhaust system (including until muffler)	Documents
Oil drain valve	Starting batteries (maintenance-free & watering-free) with connective wires	Special tools

MODEL: BF-C1250**400V | 1500rpm | 50Hz****OPTIONS**

Daily fuel tank

Rainproof type

Remote control panel

Alternator heater

Soundproof type


Paralleling system

Spare parts

Trailer type


Switch box

Automatic transfer switch

DIMENSIONS & WEIGHT**Standard Configuration (open type)**

Overall Dimensions: 4400×2060×2200 mm

Weight: 7800 kg

**Soundproof Type (standard 20'ft GP container)**

Overall Dimensions: 6058×2438×2591 mm

Weight: 12800 kg

*Specifications are subject to change without notice.***BAIFA POWER (WUXI) LTD.****WEBSITE: WWW.BAIFAPOWER.COM****EMAIL: MARKETING@BAIFAPOWER.COM****TEL: +86-510-85342633**

Comprehensive Solutions For

POWER GENERATION