

**MODEL: BF-C550DQ**

**400V | 1500rpm | 50Hz**



<b>ESP</b> Standby Power	<b>550 kVA</b>	<b>PRP</b> Prime Power	<b>500 kVA</b>
<b>ENGINE</b>	<b>DCEC Cummins</b>	<b>ALTERNATOR</b>	<b>STAMFORD</b>
	<b>QSZ13-G10</b>		<b>HCI544C1</b>

### GENERAL FEATURES

Engine: DCEC Cummins QSZ13-G10

Alternator: single bearing, IP23, insulation class H

50°C radiator, fans are driven by belt, with safety guard

Dry type air filter, fuel filter & oil filter

Vibration damper

Standard control panel

24V charging alternator

Exhaust bellows, elbows, flange & muffler

Lead-acid batteries, rack and cables

User manual

**MODEL: BF-C550DQ**

**400V | 1500rpm | 50Hz**

**GENERATOR RATINGS**

Voltage	Hz	Phase	PF (COSΦ)	Standby Amps	Standby Ratings (kW / kVA)	Prime Ratings (kW / kVA)
440/254	50	3	0.8	722	440/550	400/500
415/240	50	3	0.8	765	440/550	400/500
400/230	50	3	0.8	794	440/550	400/500
380/220	50	3	0.8	836	440/550	400/500

Prime Power (PRP): Prime power is available for an unlimited number of annual hours in variable load application, in accordance with GB/T2820 (eqv ISO 8528) ; A 10% overload capability is available for a period of 1 hour within a 12-hour period of operation.

Standby Power Rating (ESP): The standby power rating is applicable for supplying emergency power for the duration of a utility power interruption. No overload, utility parallel or negotiated outage operation capability is available at this rating.

**SALES PROMISES**

Baifa Power provides a full line of brand new and high quality products. Each and every unit is strictly factory tested.

Warranty is according to our standard conditions: 15 months from the date BAIFA sold to the first buyer or one year after installation or 1000 running hours (accumulated), whichever comes first.

Service and parts are available from Baifa Power or distributors in your location.

**MODEL: BF-C550DQ****400V | 1500rpm | 50Hz****ENGINE SPECIFICATION**

Manufacturer / Model	DCEC Cummins QSZ13-G10
Air intake system	Turbo, Air/Air cooling
Fuel system	Cummins Fuel System (XPI)
Cylinder arrangement	6 in line
Displacement	13L
Bore and stroke	130*163 (mm)
Compression ratio	17.0:1
Rated speed	1500rpm
Max. Standby power at rated speed	509kW/682hp
Governor type	Electronic

**Exhaust System**

Exhaust gas flow	81.8m <sup>3</sup> /min
Exhaust temperature	547°C
Max back pressure	13kpa

**Air Intake System**

Max intake restriction	6.2kPa
Combustion air flow	30.7m <sup>3</sup> /min
Air flow required for radiator	720m <sup>3</sup> /min

**MODEL: BF-C550DQ**

**400V | 1500rpm | 50Hz**

**Fuel System**

Fuel consumption @ 100% (Prime Power) Load	191 g/kWh	99L/h
Fuel consumption @ 75% (Prime Power) Load	190 g/kWh	74L/h
Fuel consumption @ 50% (Prime Power) Load	193 g/kWh	51L/h

**Oil System**

Total oil capacity	78L
Oil consumption	≤4g/kwh
Oil sump capacity	61-75L

**Cooling System**

Coolant capacity	86L
Max water temperature	102°C

**MODEL: BF-C550DQ****400V | 1500rpm | 50Hz****ALTERNATOR SPECIFICATION**

Industrial alternators meet the requirements of the relevant parts of the BS5000, VDE 0530, NEMA MG1-22, IEC34, CSA 22.2-100 and AS1359.

**Alternator Data**

Number of Phase	3
Connecting Type	3 Phase and 4 Wires, Y type connecting
Number of Bearing	1
Power Factor	0.8
Protection Class	IP23
Altitude	≤1000m
Exciter Type	Brushless exciting
Insulation Class/Temperature Rise	H/H
Telephone Influence Factor (TIF)	< 50
THF	< 2%
Alternator Capacity	500kVA
Alternator Efficiency	93.8%

**MODEL: BF-C550DQ****400V | 1500rpm | 50Hz****GENERATING SET DATA**

Related range of voltage setting	$\geq \pm 5\%$
Steady-state voltage deviation	$\leq \pm 1\%$
Transient voltage deviation (100 % sudden power decrease)	$\leq +20\%$
Transient voltage deviation (sudden power increase)	$\leq -15\%$
Voltage recovery time (100 % sudden power decrease)	$\leq 4S$
Voltage recovery time (sudden power increase)	$\leq 4S$
Related range of frequency setting	0-5% adjustable
Steady-state frequency band	$\leq 0.5\%$
Transient frequency deviation (100 % sudden power decrease)	$\leq +10\%$
Transient frequency deviation (sudden power increase)	$\leq -7\%$
Frequency recovery time (100 % sudden power decrease)	$\leq 3S$
Frequency recovery time (sudden power increase)	$\leq 3S$

**STANDARD FEATURES**

Standard auto control system	Exhaust system (including until muffler)	Documents
Oil drain valve	Starting batteries (maintenance-free & watering-free) with connective wires	Special tools

MCCB



**MODEL: BF-C550DQ**

**400V | 1500rpm | 50Hz**

**OPTIONS**

Daily fuel tank	Rainproof type	Remote control panel
Alternator heater	Soundproof type	Paralleling system
Spare parts	Trailer type	Switch box
Automatic transfer switch		

**DIMENSIONS & WEIGHT**



**Standard Configuration (open type)**

Overall Dimensions: 3250×1400×2100mm

Weight: 3130 kg

**Soundproof Type**

Overall Dimensions: 4230×1660×2350 mm

Weight: 4350 kg

*Specifications are subject to change without notice.*

**BAIFA POWER (WUXI) LTD.**  
**WEBSITE: WWW.BAIFAPOWER.COM**  
**EMAIL: MARKETING@BAIFAPOWER.COM**  
**TEL: +86-510-85342633**

Comprehensive Solutions For  
**POWER GENERATION**

