

MODEL: BF-SM2500

400V | 1500rpm | 50Hz



ESP Standby Power	2500 kVA	PRP Prime Power	2250 kVA
ENGINE	MITSUBISHI	ALTERNATOR	STAMFORD
	S16R2-PTAW-C		S7L1D-H41

GENERAL FEATURES

Engine: MITSUBISHI S16R2-PTAW-C

Alternator: single bearing, IP23, insulation class H

40°C radiator, fans are driven by belt, with safety guard

Dry type air filter, fuel filter & oil filter

Vibration damper

Standard control panel

24V charging alternator

Exhaust bellows, elbows, flange & muffler

Lead-acid batteries, rack and cables

User manual

MODEL: BF-SM2500**400V | 1500rpm | 50Hz****GENERATOR RATINGS**

Voltage	Hz	Phase	PF (COS Φ)	Standby Amps	Standby Ratings (kW / kVA)	Prime Ratings (kW / kVA)
440/254	50	3	0.8	3280	2000kW/2500kVA	1800kW/2250kVA
415/240	50	3	0.8	3478	2000kW/2500kVA	1800kW/2250kVA
400/230	50	3	0.8	3609	2000kW/2500kVA	1800kW/2250kVA
380/220	50	3	0.8	3798	2000kW/2500kVA	1800kW/2250kVA

Prime Power (PRP): Prime power is available for an unlimited number of annual hours in variable load application, in accordance with GB/T2820 (eqv ISO 8528) ; A 10% overload capability is available for a period of 1 hour within a 12-hour period of operation.

Standby Power Rating (ESP): The standby power rating is applicable for supplying emergency power for the duration of a utility power interruption. No overload, utility parallel or negotiated outage operation capability is available at this rating.

SALES PROMISES

Baifa Power provides a full line of brand new and high quality products. Each and every unit is strictly factory tested.

Warranty is according to our standard conditions: 15 months from the date BAIFA sold to the first buyer or one year after installation or 1000 running hours (accumulated), whichever comes first.

Service and parts are available from Baifa Power or distributors in your location.

MODEL: BF-SM2500**400V | 1500rpm | 50Hz****ENGINE SPECIFICATION**

Manufacturer / Model	Mitsubishi S16R2-PTAW-C
Air intake system	Turbo, Water/Air Cooling
Fuel system	Bosch PS8
Cylinder arrangement	16 in "V"
Displacement	79.9L
Bore and stroke	170×220 (mm)
Compression ratio	14
Rated speed	1500rpm
Max. Standby power at rated speed	2167KW/2905HP
Governor type	Electronic

Exhaust System

Exhaust gas flow	498 m ³ /min
Exhaust temperature	520 °C
Max back pressure	5.8kPa

Air Intake System

Max intake restriction	6.0kPa
Combustion air flow	188 m ³ /min
Air flow required for radiator	2700 m ³ /min

MODEL: BF-SM2500

400V | 1500rpm | 50Hz

Fuel System

Fuel consumption @ 100% (Prime Power) Load	209g/kWh	476 L/h
Fuel consumption @ 75% (Prime Power) Load	N/A	N/A
Fuel consumption @ 50% (Prime Power) Load	N/A	N/A

Oil System

Total oil capacity	290L
Oil consumption	0.8g/kwh
Oil sump capacity	200~260L

Cooling System

Coolant capacity	550L
Max water temperature	98°C

MODEL: BF-SM2500**400V | 1500rpm | 50Hz****ALTERNATOR SPECIFICATION**

Industrial alternators meet the requirements of the relevant parts of the BS5000, VDE 0530, NEMA MG1-22, IEC34, CSA 22.2-100 and AS1359.

Alternator Data

Number of Phase	3
Connecting Type	3 Phase and 4 Wires, Y type connecting
Number of Bearing	1
Power Factor	0.8
Protection Class	IP23
Altitude	≤1000m
Exciter Type	Brushless exciting
Insulation Class/Temperature Rise	H/H
Telephone Influence Factor (TIF)	<50
THF	<2%
Alternator Capacity	2325kVA
Alternator Efficiency	96.2%

MODEL: BF-SM2500**400V | 1500rpm | 50Hz****GENERATING SET DATA**

Related range of voltage setting	$\geq \pm 5\%$
Steady-state voltage deviation	$\leq \pm 1\%$
Transient voltage deviation (100 % sudden power decrease)	$\leq +25\%$
Transient voltage deviation (sudden power increase)	$\leq -20\%$
Voltage recovery time (100 % sudden power decrease)	$\leq 6S$
Voltage recovery time (sudden power increase)	$\leq 6S$
Related range of frequency setting	0-5% adjustable
Steady-state frequency band	$\leq 1.5\%$
Transient frequency deviation (100 % sudden power decrease)	$\leq +12\%$
Transient frequency deviation (sudden power increase)	$\leq -10\%$
Frequency recovery time (100 % sudden power decrease)	$\leq 5S$
Frequency recovery time (sudden power increase)	$\leq 5S$

STANDARD FEATURES

Standard auto control system	Exhaust system (including until muffler)	Documents
Oil drain valve	Starting batteries (maintenance-free & watering-free) with connective wires	


MODEL: BF-SM2500

400V | 1500rpm | 50Hz

OPTIONS

Daily fuel tank	Rainproof type	Remote control panel
Alternator heater	Soundproof type	Paralleling system
Spare parts	Trailer type	Switch box
Automatic transfer switch		

DIMENSIONS & WEIGHT



Standard Configuration (open type)
Overall Dimensions: 5800×2210×2600 mm
Weight: 16800 kg

Specifications are subject to change without notice.

BAIFA POWER (WUXI) LTD.
WEBSITE: WWW.BAIFAPOWER.COM
EMAIL: MARKETING@BAIFAPOWER.COM
TEL: +86-510-85342633